Honeywell

Genetron Performax® LT (R-407F)

ersion 1.6		Revision Date 09/28/2015	Print Date 10/07/201
ECTION 1. PRODUCT AND CO	OMP	ANY IDENTIFICATION	
Product name	:	Genetron Performax® LT (R-407F)	
Number	:	00000013866	
Product Use Description	:	Refrigerant	
Manufacturer or supplier's details	:	Honeywell International Inc. 101 Columbia Road Morristown, NJ 07962-1057	
For more information call	:	800-522-8001 +1-973-455-6300 (Monday-Friday, 9:00am-5:00pm)	
In case of emergency call	:	Medical: 1-800-498-5701 or +1-303-3 Transportation (CHEMTREC): 1-800 527-3887	
	:	(24 hours/day, 7 days/week)	
ECTION 2. HAZARDS IDENTIF		TION	
Emergency Overview			
Form		: Liquefied gas	
Color		: clear and colourless	
Odor		: ether-like	
Classification of the substa	ince	e or mixture	
Classification of the		: Gases under pressure, Liquefied ga	S
substance or mixture		Simple Asphyxiant	
GHS Label elements, inclu	din	g precautionary statements	
Symbol(s)			
		Page 1 / 14	

Honeywell

Genetron Performax® LT (R-407F) 000000013866

0000013866			
ersion 1.6	Revision Date 09/28/2015		Print Date 10/07/20
Signal word	: Warning		
Hazard statements	: Contains gas under pressur May displace oxygen and c		
Precautionary statements	: Storage: Protect from sunlight. Store	in a well-ve	entilated place.
Hazards not otherwise classified	: May cause frostbite. May cause cardiac arrhythr May cause eye and skin irri		
Carcinogenicity			
or anticipated carcinogen by N		equal to 0.1	% is identified as a know
CTION 3. COMPOSITION/INF	ORMATION ON INGREDIENTS		
Synonyms	: Mixture of 1,1,1,2-Tetrafluoro Difluoromethane	bethane, Pe	entafluoroethane and
Synonyms Chemical nature		bethane, Pe	entafluoroethane and
	Difluoromethane : Mixture	bethane, Pe S-No.	entafluoroethane and Concentration
Chemical nature	Difluoromethane : Mixture Name CAS		
Chemical nature Chemical N	Difluoromethane : Mixture <u>Name CA</u> 811	S-No.	Concentration
Chemical nature Chemical N 1,1,1,2-Tetrafluoroethane	Difluoromethane : Mixture Name CAS 811 75	<u>S-No.</u> -97-2	Concentration 40.00 %
Chemical nature Chemical N 1,1,1,2-Tetrafluoroethane Difluoromethane	Difluoromethane : Mixture Name CAS 811 75 354	<u>S-No.</u> -97-2 -10-5	Concentration 40.00 % 30.00 %
Chemical nature Chemical N 1,1,1,2-Tetrafluoroethane Difluoromethane Pentafluoroethane	Difluoromethane : Mixture Name CAS 811 75 354	S-No. -97-2 -10-5 -33-6 is irregular n. Use oxyg is present.	Concentration 40.00 % 30.00 % 30.00 % or stopped, jen as required, Call a physician. Do
Chemical nature Chemical N 1,1,1,2-Tetrafluoroethane Difluoromethane Pentafluoroethane ECTION 4. FIRST AID MEASUR	Difluoromethane : Mixture Name CAS 811 75 354 RES : Move to fresh air. If breathing administer artificial respiratior provided a qualified operator	<u>S-No.</u> -97-2 -10-5 -33-6 is irregular n. Use oxyg is present. e-ephedrine immediately	Concentration 40.00 % 30.00 % 30.00 % 30.00 % or stopped, gen as required, Call a physician. Do group.

Honeywell

Genetron Performax® LT (R-407F)

sion 1.6		Revision Date 09/28/2015 Print Date 10/07/20
51011 1.0		lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
Eye contact	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
Ingestion	:	Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.
Notes to physician		
Treatment	:	Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost- bitten areas as needed.
TION 5. FIREFIGHTING MEA	SU	RES
TION 5. FIREFIGHTING MEA		RES The product is not flammable. ASHRAE 34 Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
	:	The product is not flammable. ASHRAE 34 Use water spray, alcohol-resistant foam, dry chemical or
Suitable extinguishing media Specific hazards during	:	 The product is not flammable. ASHRAE 34 Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. This product is not flammable at ambient temperatures and atmospheric pressure. However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources. Contents under pressure. Container may rupture on heating. Cool closed containers exposed to fire with water spray. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. In case of fire hazardous decomposition products may be produced such as: Hydrogen fluoride Carbon monoxide Carbon dioxide (CO2)
Suitable extinguishing media Specific hazards during firefighting	:	 The product is not flammable. ASHRAE 34 Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. This product is not flammable at ambient temperatures and atmospheric pressure. However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources. Container may rupture on heating. Cool closed containers exposed to fire with water spray. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. In case of fire hazardous decomposition products may be produced such as: Hydrogen fluoride Carbon monoxide Carbon dioxide (CO2) Carbonyl halides

SAFETY DATA SHEET		Honeywell
Genetron Performax®	LT (R-407F)	
00000013866		
Version 1.6	Revision Date 09/28/2015 circumstances and the surrounding	Print Date 10/07/2015 environment.
SECTION 6. ACCIDENTAL RELE		
Personal precautions	: Wear personal protective equipment. Immediately evacuate personnel to s Keep people away from and upwind Remove all sources of ignition. Avoid skin contact with leaking liquid Ventilate the area. After release, disperses into the air. Vapours are heavier than air and car reducing oxygen available for breathi Avoid accumulation of vapours in low Unprotected personnel should not rel tested and determined safe. Ensure that the oxygen content is >=	of spill/leak. (danger of frostbite). n cause suffocation by ng. v areas. turn until air has been
Environmental precautions	: Prevent further leakage or spillage if The product evapourates readily.	safe to do so.
Methods for cleaning up	: Ventilate the area.	
SECTION 7. HANDLING AND ST	ORAGE	
Handling		
Handling Advice on protection	 Wear personal protective equipment. Do not breathe vapour. Avoid contact with skin, eyes and clo Follow all standard safety precautions compressed gas cylinders. Keep away from heat. Use authorized cylinders only. Protect cylinders from physical dama Do not puncture or drop cylinders, ex or excessive heat. Do not pierce or burn, even after use flame or any incandescent material. Do not remove screw cap until immed Always replace cap after use. The product is not flammable. 	s for handling and use of ge. pose them to open flame . Do not spray on a naked diately ready for use.
against fire and explosion	Can form a combustible mixture with atmospheric pressure.	air at pressures above

Honeywell

Genetron Performax® LT (R-407F)

rsion 1.6	Revision Date 09/28/2015	Print Date 10/07/20
Storage		
Requirements for storage areas and containers	 Pressurized container: protect from to temperatures exceeding 50 °C after use. Keep containers tightly closed in place. Storage rooms must be properly Ensure adequate ventilation, esp Protect cylinders from physical d 	 Do not pierce or burn, even a dry, cool and well-ventilated ventilated. becially in confined areas.
CTION 8. EXPOSURE CONT	ROLS/PERSONAL PROTECTION	
Protective measures	: Do not breathe vapour. Avoid contact with skin, eyes and Ensure that eyewash stations an the workstation location.	-
Engineering measures	: General room ventilation is adeq Perform filling operations only at ventilation facilities.	
Eye protection	: Wear as appropriate: Safety glasses with side-shields If splashes are likely to occur, we Goggles or face shield, giving co	
Hand protection	 Leather gloves In case of contact through splash Protective gloves Neoprene gloves Polyvinyl alcohol or nitrile- butyl- 	-
Skin and body protection	: Avoid skin contact with leaking li Wear cold insulating gloves/ face	
Respiratory protection	 In case of insufficient ventilation equipment. Wear a positive-pressure supplie Vapours are heavier than air and reducing oxygen available for bre For rescue and maintenance woo contained breathing apparatus. 	ed-air respirator. I can cause suffocation by eathing.
Hygiene measures	 Handle in accordance with good practice. Ensure adequate ventilation, esp Do not get in eyes, on skin, or or Remove and wash contaminated 	pecially in confined areas.

Honeywell

Genetron Performax® LT (R-407F)

00000013866

ion 1.6		Revision Date			Print Date 10/07/2
	Ke	ep working c	lothes separately		
Exposure Guidelir	les				
Components	CAS-No.	Value	Control parameters	Upda te	Basis
1,1,1,2- Tetrafluoroethane	811-97-2	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1,2- Tetrafluoroethane	811-97-2	TWA : Time weighted average	4,240 mg/m3 (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
Pentafluoroethan e	354-33-6	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
Difluoromethane	75-10-5	TWA : Time weighted average	2,200 mg/m3 (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
Difluoromethane	75-10-5	TWA : Time weighted average	(1,000 ppm)	1994	Honeywell:Limit established by Honeywell International Inc.
FION 9. PHYSICAL Physical state Color Odor	: Li : cl	L PROPERT quefied gas ear and colou ther-like	-		
θΗ	: N	ote: neutral			
Boiling point/boiling	range · -	45.5 °C at 1,0)13 hPa		

Page 6 / 14

Honeywell

Genetron Performax® LT (R-407F) 000000013866

rsion 1.6	Revision Date 09/28/2015	Print Date 10/07/2
Flash point	: Note: Not applicable	
Lower explosion limit	: Note: None	
Upper explosion limit	: Note: None	
Vapor pressure	: 10,218 hPa at 21.1 °C(70.0 °F) 24,621 hPa at 54.4 °C(129.9 °F)	
Vapor density	: Note: not determined	
Density	: Note: not determined	
Partition coefficient: n- octanol/water	: log Pow: 1.06 Note: 1,1,1,2-tetrafluoroethane (HFC-134a log Pow: 1.48 Note: Ethane, pentafluoro- (HFC-125))
Ignition temperature	: Note: no data available	
CTION 10. STABILITY AND	REACTIVITY	
Chemical stability	: Stable under normal conditions.	
Possibility of hazardous reactions Conditions to avoid	 Hazardous polymerisation does not occur. Pressurized container. Protect from sunlig expose to temperatures exceeding 50 °C. Decomposes under high temperature. Some risk may be expected of corrosive a decomposition products. 	ht and do not

Honeywell

Genetron Performax® LT (R-407F)

Manajara 4.0	Devision Data 00/00/0045
Version 1.6	Revision Date 09/28/2015 Print Date 10/07/2015 Can form a combustible mixture with air at pressures above
	atmospheric pressure.
	Do not mix with oxygen or air above atmospheric pressure.
Incompatible materials to	: Potassium
avoid	Calcium
	Powdered metals Finely divided aluminium
	Finely divided magnesium
	Zinc
Hazardous decomposition	: In case of fire hazardous decomposition products may be
products	produced such as:
	Gaseous hydrogen fluoride (HF). Carbonyl halides
	Carbon monoxide
	Carbon dioxide (CO2)
SECTION 11. TOXICOLOGICAL	NFORMATION
Acute inhalation toxicity	
1,1,1,2-Tetrafluoroethane	: LC50: > 500000 ppm
	Exposure time: 4 h
	Species: Rat
Difluoromethane	: LC50: > 520000 ppm
	Exposure time: 4 h
	Species: Rat
Pentafluoroethane	: > 769000 ppm
	Exposure time: 4 h
	Species: Rat
Sensitisation	
1,1,1,2-Tetrafluoroethane	: Cardiac sensitization
, , ,	Species: dogs
	Note: No-observed-effect level
	50 000 ppm Lowest observed effect level
	75 000 ppm
Difluoromethane	: Cardiac sensitization
	Species: dogs
	Note: No-observed-effect level >350 000 ppm
Pentafluoroethane	: Cardiac sensitization
	Page 8 / 14

Honeywell

Genetron Performax® LT (R-407F)

Varaian 1.6	Devision Data 00/28/2015	Drint Data 10/07/2015
Version 1.6	Revision Date 09/28/2015 Species: dogs	Print Date 10/07/2015
	Note: No-observed-effect level	
	75 000 ppm	
	Lowest observed effect level 100 000 ppm	
Repeated dose toxicity 1,1,1,2-Tetrafluoroethane	: Species: Rat	
	NOEL: 40000 ppm	
Difluoromethane	: Species: Rat Application Route: Inhalation	
	Exposure time: (90 d)	
	NOEL: 50000 ppm	
	Subchronic toxicity	
Pentafluoroethane	Species: Rat	
	Application Route: Inhalation	
	Exposure time: (4 Weeks)	
	NOEL: 50000 ppm Subchronic toxicity	
Constaviaity in vitra		
Genotoxicity in vitro 1,1,1,2-Tetrafluoroethane :	Note: In vitro tests did not show mutagen	ic effects
	-	
Difluoromethane :	Test Method: Ames test	
	Result: negative	
Pentafluoroethane :	Test Method: Ames test	
	Result: negative	
:	Cell type: Human lymphocytes	
	Result: negative	
	Method: Mutagenicity (in vitro mammalia	n cytogenetic test)
:	Test Method: Chromosome aberration te	st in vitro
	Result: negative	
:	Cell type: Human lymphocytes	
	Result: negative	
	-	
:	Cell type: Chinese Hamster Ovary Cells Result: negative	
	Nesult. Heyalive	
Genotoxicity in vivo Difluoromethane :	Species: Mouse	
	Cell type: Bone marrow	
	Method: Mutagenicity (micronucleus test)
	Page 9 / 14	

Honeywell

Genetron Performax® LT (R-407F) 000000013866

rsion 1.6	Revision Date 09/28/2015	Print Date 10/07/20
	Result: negative	
-		
Teratogenicity Difluoromethane	: Species: Rat	
Diridoromethane	Dose: NOEL - 50,000 ppm	
	Note: Did not show teratogenic effect	s in animal experiments.
	Species: Rabbit	
	Dose: NOEL - 50,000 ppm Note: Did not show teratogenic effect	s in animal experiments
Pentafluoroethane	: Species: Rabbit	K 0
	Application Route: Inhalation exposu NOAEL,Teratog: 50,000 ppm	
	NOAEL, Maternal: 50,000 ppm	
	Note: Did not show teratogenic effect	s in animal experiments.
	Species: Rat	
	Application Route: Inhalation exposu	re
	NOAEL,Teratog: 50,000 ppm NOAEL,Maternal: 50,000 ppm	
	NOAEL, Maternal: 50,000 ppm Note: Did not show teratogenic effect	s in animal experiments.
	0	•
Further information	: Note: Vapours are heavier than air a	nd can cause suffocation
	by reducing oxygen available for brea	athing. Rapid evaporation
	of the liquid may cause frostbite. May arrhythmia.	cause cardiac
CTION 12. ECOLOGICAL I	NFORMATION	
Biodegradability		
Difluoromethane	: Note: Minimal	
Pentafluoroethane	: Result: Not readily biodegradable.	
	Value: 5 %	
	Method: OECD 301 D	
Further information on e	cology	
	: This product is subject to U.S. Enviro	nmental Protection
Additional ecological		
	Agency Clean Air Act Regulations at	
Additional ecological	Agency Clean Air Act Regulations at This product contains greenhouse ga	ises which may
Additional ecological	Agency Clean Air Act Regulations at	ises which may Γ vent to the atmosphere.

Honeywell

Genetron Performax® LT (R-407F)

Version 1.6		Revision Date 09/28/2015	Print Date 10/07/2015
	r	esidual must be recovered.	
SECTION 13	DISPOSAL CONSIDERAT		
SECTION 13.	DISPUSAL CONSIDERAL	IONS	
Disposal		Deserve all Federal, State, and Loca	al Environmental
Note		This product is subject to U.S. Enviro Agency Clean Air Act Regulations S 32 regarding refrigerant recycling.	
SECTION 14.	TRANSPORT INFORMAT	ION	
DOT	UN/ID No. Proper shipping name	 : UN 3163 : LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane) 	
	Class Packing group Hazard Labels	2.2 2.2	
ΙΑΤΑ	UN/ID No. Description of the goods	: UN 3163 : LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane)	
	Class Hazard Labels Packing instruction (car aircraft)	: 2.2 : 2.2 go : 200	
	Packing instruction (passenger aircraft)	: 200	
IMDG	UN/ID No. Description of the goods	(1,1,1,2-TETRAFLUOROE	
	Class Hazard Labels EmS Number Marine pollutant	: 2.2 : 2.2 : F-C, S-V : no	
SECTION 15.	REGULATORY INFORMA	TION	
Inventori	es		
		Page 11 / 14	

Honeywell

Genetron Performax® LT (R-407F)

Version 4.0	Devision Data 00/20/2015	Drint Data 40/07/2015
Version 1.6	Revision Date 09/28/2015	Print Date 10/07/2015
US. Toxic Substances Control Act	: On TSCA Inventory	
Australia. Industrial Chemical (Notification and Assessment) Act	: On the inventory, or in compliance with the	ne inventory
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)	: All components of this product are on the	Canadian DSL.
Japan. Kashin-Hou Law List	: On the inventory, or in compliance with the	ne inventory
Korea. Toxic Chemical Control Law (TCCL) List	: On the inventory, or in compliance with the	ne inventory
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	: On the inventory, or in compliance with the	ne inventory
China. Inventory of Existing Chemical Substances	: On the inventory, or in compliance with the	ne inventory
New Zealand. Inventory of Chemicals (NZloC), as published by ERMA New Zealand	: On the inventory, or in compliance with the	ne inventory
National regulatory informa	tion	
SARA 302 Components	: No chemicals in this material are subject requirements of SARA Title III, Section 30	
SARA 313 Components	: This material does not contain any chemic known CAS numbers that exceed the three reporting levels established by SARA Title	eshold (De Minimis)
SARA 311/312 Hazards	: Sudden Release of Pressure Hazard Acute Health Hazard	
	Page 12 / 14	

AFETY DATA SHEET			Honeywell
enetron Performax®	LT (R-40 ⁻	7F)	
0000013866			
ersion 1.6		on Date 09/28/2015	Print Date 10/07/20
California Prop. 65	: WARNING! This product conta State of California to cause ca Dichloromethane		
	: WARNING: This product contains a chemical know State of California to cause birth defects or other re harm.		
	Chlorom	ethane	74-87-3
Massachusetts RTK	: Dichlorom	ethane	75-09-2
New Jersey RTK	: Difluorome		75-10-5
Pennsylvania RTK	: Difluorome	ethane	75-10-5
WHMIS Classification	: A: Compressed Gas This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.		
CTION 16. OTHER INFORMAT	TION		
Liselth harved	HMIS III	NFPA	
Health hazard Flammability	: 1 : 1	2 1	
Physical Hazard Instability	: 0	0	
Hazard rating and rating systuse of individuals trained in t			mation is intended solely for the
Further information			
The information provided in the information and belief at the or guidance for safe handling.	late of its pub	lication. The information	
		$_{1}$, $_{1}$, $_{1}$, $_{1}$, $_{2}$, $_{1}$, $_{2}$, $_{1}$, $_{2}$, $_{1}$, $_{2}$, $_{2}$, $_{2}$, $_{1}$, $_{2}$	

Honeywell

Genetron Performax® LT (R-407F)

00000013866

Version 1.6

Revision Date 09/28/2015

Print Date 10/07/2015

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 06/04/2014

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group